2015-2022 Chevy Colorado/GMC Canyon Diff Drop Instructions
2023+ Chevy Colorado/GMC Canyon Diff Drop Instructions

Parts List:

- (2) 2 piece diff spacers
- (2) M14 Bolts
- (2) Washers
- (2) Button Head Screws
- Loctite for screws

Tools Needed:

- 22mm socket
- Allen Socket or Wrench for Diff Screws

Approximate Installation Time: 30 minutes

Note:

- Only qualified mechanics experienced in the installation and removal of suspension components should perform this installation
- Uses of a house is highly recommended and will substantially reduce installation time
- Never work on or under a vehicle unless it properly support by safety stands and wheels are blocked

- Never use impact wrenches or impact drivers to install or remove shock absorber piston components, shafts or piston rod nuts

Installation:

1. Block the rear wheels, lift the front of the vehicle and place jack stands or use automotive lift
2. Remove front wheels (not 100% necessary but easier to do without the wheels)
3. Remove the 22mm bolt on the drivers side and replace it with the longer bolt that we provide. Repeat the same on the passenger side

4. Once the longer bolts are in place, lower the diff by backing out the bolts but don't remove them.

5. Insert the diff spacer around the lowered bolt and center it

6. Put a dab of loctite on the screws and insert them into the diff spacer, tighten until tight no need for overdoing it
7. Tighten the lower bolt

8. Replace the wheels if removed and remove the jack stands

RELEASE OF LIABILITY

I, the customer, do hereby release and forever discharge Peak Suspension, their agents, employees, successors and assigns, and their respective heirs, personal representatives, affiliates, successors and assigns, and any and all persons, firms or corporations liable or who might be claimed to be liable, whether or not herein named, from any and all claims, demands, damages, actions, causes of action or suits of any kind or nature whatsoever, whether known or unknown, fixed or contingent, which I now have or may hereafter have or claim to have, as a result of or in any way relating to the following: Parts sold & installed by Peak Suspension or parts sold & installed by end user; any parts sold online, any parts sold online or installed by a reseller, any parts installed by an installation shop. It is understood and agreed that this payment is made and received in full and complete settlement and satisfaction of the aforesaid actions, causes of action, claims and demands; that this Release contains the entire agreement between the parties; and that the terms of this Agreement are contractual and not merely a recital. Furthermore, this Release shall be binding upon the undersigned, and his respective heirs, executors, administrators, personal representatives, successors and assigns. This Release shall be subject to and governed by the laws of the State of California.

PRODUCT SAFETY WARNING: Peak Suspension strongly recommends the installation of products be done by a certified mechanic. If this does not occur, be certain the person(s) installing the product read, understand and follow all instructions and warnings pertaining to the application before installation. Do not add, alter, or fabricate any factory or aftermarket parts to increase vehicle height over the intended height of the Peak Suspension product purchased. Mixing component brands is not recommended.

Installation of suspension lift kits or any other lifting kits or devices will raise the center of gravity. For this reason, Peak Suspension urges that extreme caution be used when encountering driving conditions which may cause vehicle imbalance. Furthermore, the driver's field of vision and judgment will not be as good due to the height of the vehicle. Due to the installation of larger tires, the speedometer will read slower than the actual speed being traveled and more distance will be required to stop the vehicle. It is the owner's responsibility to caution and warn any potential driver of the vehicle about these driving and handling conditions. Peak Suspension will not be held liable or responsible for damages or personal injuries resulting from the use of lifting devices and or related products. The tires and rims should be changed to sufficiently increase the vehicle's total overall width and stability to help accommodate lifting devices.

Peak Suspension aftermarket suspension products and accessories modify a vehicle for uses which exceed conditions anticipated by the vehicle manufacturer. The uses include the high performance demands required during offroad. These conditions vary in the degree of extremity and cannot be controlled by the vehicle or product manufacturer. If the components within the suspension system or accessories become worn due to frequent and/or extreme use, the safety and reliability of the vehicle is at risk. The maintenance of aftermarket equipment to ensure the vehicle occupants safety is entirely your responsibility. Do not purchase Peak Suspension products unless you are willing to accept this responsibility. Do not install any Peak Suspension suspension products or accessories unless you feel competent at installing the product without causing present or future injury to yourself or other vehicle occupants; seek an authorized installation center.

Most states have some type of law limiting vehicle height. The amount of lift allowed, and how the lift can be achieved, varies greatly. Several states offer exemptions for farm and commercial registered vehicles. It is the vehicle owner's responsibility to check state and local laws to ensure that their vehicle will be in compliance. Peak Suspension reserves the right to make changes in design, materials and specifications as deemed necessary without prior notice and without assuming obligation to modify any product previously manufactured. Obligation or liabilities will not be assumed with respect to similar products previously advertised.

This Release of Liability and Product Safety Warning has been read and fully understood by the undersigned and has been explained to me